

Technical drawing of the 116.2 System (long) showing a side view of a mechanical assembly. The drawing includes the following dimensions:

- Overall length: 45 ± 1.5
- Distance from front flange to first internal step: $11.5 - 0.5$
- Distance between internal steps: $26^{+0}_{-1.5}$
- Distance from front flange to rear flange: 8.5 ± 1.5
- Distance from front flange to rear flange (alternative measurement): $11.85 - 0.5$
- Distance from front flange to rear flange (alternative measurement): 104.35 ± 1.35
- Distance from front flange to rear flange (alternative measurement): 9.95 ± 0.5
- Distance from front flange to rear flange (alternative measurement): 5 ± 0.3

Technical drawing of a 93.8 System aenge (93.8 System aenge) showing a side view and a cross-section. The side view shows a long cylindrical component with a flange at the top. The cross-section shows a central bore. Dimensions are given in millimeters.

Dimensions (mm):

- Overall length: 93.8
- Flange thickness: 45.7 ± 1.5
- Flange outer diameter: $\varnothing 27.8 \pm 0.3$
- Flange inner diameter: $\varnothing 27.4 \pm 0.3$
- Flange bore diameter: $\varnothing 25.5 \pm 0.3$
- Flange bore length: 36.4 ± 1.1
- Flange bore depth: 77.05 ± 1
- Flange bore diameter: $\varnothing 17.2 \pm 0.5$
- Flange bore length: 68.8 ± 1.5
- Flange bore diameter: $\varnothing 8.5 \pm 0.3$

[illegible][illegible]

Technical drawing of a 12V Oberlenke SAE fuel injector. The drawing shows a side view of the injector with various dimensions and labels. Key dimensions include:

- 116,5^{+0,6}_{-0,6}
- 16,2^{+0,2}_{-0,1}
- 36 ± 0,3
- 5 ± 0,2
- 88,5 ± 0,2
- 87,5 ± 0,6
- 97,15 ± 0,6
- 118,6 ± 0,8
- 45 ± 1,5
- 121,2 ± 0,5
- 117,2 ± 0,5
- Ø 8,5 ± 0,3
- 12V Oberlenke SAE
- Dichtflaeche Zundkerze